


PROJECT ID: 9877-03-71
WITH: N.A.

COUNTY: ONEIDA

ORDER OF SHEETS

Section No.	1	Title
Section No.	2	Typical Sections and Details
Section No.	3	Estimate of Quantities
Section No.	3	Miscellaneous Quantities
Section No.	4	Right of Way Plat
Section No.	5	Plan and Profile
Section No.	6	Standard Detail Drawings
Section No.	7	Sign Plates
Section No.	8	Structure Plans
Section No.	9	Computer Earthwork Data
Section No.	9	Cross Sections

TOTAL SHEETS =



DESIGN DESIGNATION 9877-03-01

A.A.D.T.	2026	=	72
A.A.D.T.	2046	=	78
D.H.V.		=	8
D.D.		=	50/50
T.		=	10.0%
DESIGN SPEED		=	45 MPH
ESALS		=	15,000

CONVENTIONAL SYMBOLS

PLAN

CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE

GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



PLAN OF PROPOSED IMPROVEMENT

HAYMEADOW CREEK BRIDGE, P-43-0058

MALVERN FIRE LN - USH 8/STH 47

T PELICAN, HAYMEADOW ROAD
ONEIDA COUNTY

STATE PROJECT NUMBER
9877-03-71



TOTAL NET LENGTH OF CENTERLINE = 0.030 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), ONEIDA COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 12A.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
9877-03-71		

ORIGINAL PLANS PREPARED BY

 **Short Elliott Hendrickson Inc.**
6808 Odana Road, Suite 200
Madison, WI 53719-1137
608.620.6199 main | 888.908.8166 fax
Building a Better World for All of Us™ 800.732.4362 toll free | www.sehinc.com

PRELIMINARY
30% REVIEW
NOT FOR BIDDING OR
CONSTRUCTION

(Date) (Signature)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY	
Surveyor	SEH
Designer	SEH
Project Manager	
Regional Examiner	
Regional Supervisor	

APPROVED FOR THE DEPARTMENT

DATE: (Signature)

E

STANDARD ABBREVIATIONS:

ABUT	ABUTMENT	ID	INSIDE DIAMETER
AC	ACRE	INV	INVERT
AGG	AGGREGATE	IP	IRON PIPE ON PIN
AECPRC	APRON ENDWALL FOR CULVERT PIPE REINFORCED CONCRETE	LHF	LEFT-HAND FORWARD
AECPCS	APRON ENDWALL FOR CULVERT PIPE CORRUGATED STEEL	L	LENGTH OF CURVE
ASPH	ASPHALTIC	LF	LINEAR FOOT
AVG	AVERAGE	LC	LONG CHORD OF CURVE
ADT	AVERAGE DAILY TRAFFIC	LS	LUMP SUM
BF	BACK FACE	MH	MANHOLE
BM	BENCH MARK	MOR	MID POINT OF RADIUS
BR	BRIDGE	NC	NORMAL CROWN
CE	COMMERCIAL ENTRANCE	NO	NUMBER
C/L	CENTER LINE	OBLIT	OBLITERATE
Δ	CENTRAL ANGLE OR DELTA	PAVT	PAVEMENT
COB	CENTER OF BARRIER	PE	PRIVATE ENTRANCE
CONC	CONCRETE	PVRC	POINT OF VERTICAL REVERSE CURVE
CPRC	CULVERT PIPE REINFORCED CONCRETE	QOR	QUARTER POINT OF RADIUS
CPRCHE	CULVERT PIPE REINFORCED CONCRETE HORIZONTAL ELLIPTICAL	R	RADIUS
CR	CREEK	REQ'D	REQUIRED
CY	CUBIC YARD	RES	RESIDENCE OR RESIDENTIAL
C&G	CURB AND GUTTER	RHF	RIGHT-HAND FORWARD
D	DEGREE OF CURVE	R/W	RIGHT-OF-WAY
DHV	DESIGN HOUR VOLUME	R	RIVER
DISCH	DISCHARGE	RDWY	ROADWAY
DG	DITCH GRADE	R/L	REFERENCE LINE
DWY	DRIVEWAY	SALV	SALVAGED
X	EAST GRID COORDINATE	SAN	SANITARY SEWER
EAT	STEEL PLATE BEAM GUARD ENERGY ABSORBING TERMINAL	SF	SQUARE FEET
EOR	END POINT OF RADIUS	SY	SQUARE YARD
EL	ELEVATION	SDD	STANDARD DETAIL DRAWINGS
ENT	ENTRANCE	STA	STATION
ESALS	EQUIVALENT SINGLE AXLE LOADS	SS	STORM SEWER
EXC	EXCAVATION	SSPRC	STORM SEWER PIPE REINFORCED CONCRETE
EBS	EXCAVATION BELOW SUBGRADE	SE	SUPERELEVATION RATE
EXIST	EXISTING	TC	TOP OF CURB
FC	FACE OF CURB	T OR TN	TOWN
FF	FACE TO FACE	T	TRUCKS (PERCENT OF)
FERT	FERTILIZE	TYP	TYPICAL
FE	FIELD ENTRANCE	VAR	VARIABLE
FL	FLOW LINE	VC	VERTICAL CURVE
FO	FIBER OPTIC	Y	NORTH GRID COORDINATE
CWT	HUNDREDWEIGHT	YD	YARD
HYD	HYDRANT		

RUNOFF COEFFICIENT TABLE

	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)		
LAND USE:	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER
ROW CROPS	.08	.16	.22	.12	.20	.27	.15	.24	.33	.19	.28	.38
	.22	.30	.38	.26	.34	.44	.30	.37	.50	.34	.41	.56
MEDIAN STRIP- TURF	.19	.20	.24	.19	.22	.26	.20	.23	.30	.20	.25	.30
	.24	.26	.30	.25	.28	.33	.26	.30	.37	.27	.32	.40
SIDE SLOPE- TURF			.25			.27			.28			.30
			.32			.34			.36			.38
PAVEMENT:												
ASPHALT						.70 - .95						
CONCRETE						.80 - .95						
BRICK						.70 - .80						
DRIVES, WALKS						.75 - .85						
ROOFS						.75 - .95						
GRAVEL ROADS, SHOULDERS						.40 - .60						

TOTAL PROJECT AREA = __. __ ACRES
TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = __. __ ACRES

DNR AREA LIAISON:

WI DEPT OF NATURAL REASOURCES
DNR NORTHERN REGION HEADQUARTERS
107 SUTLIFF AVENUE
RHINELANDER, WI 54501
TELEPHONE: 715.365.8916
ATTENTION: WENDY HENNIGES
EMAIL: WENDY.HENNIGES@WISCONSIN.GOV

TOWN OF PELICAN:

TOWN CHAIRMAN
4095 PINE LANE
RHINELANDER, WI 54501
TELEPHONE: 715.360.0493
ATTENTION: DAVE HOLLANDS
EMAIL: DHOLLANDS@PELICANFIRE.COM

UTILITY CONTACT LIST:

NO KNOWN UTILITIES IN THE PROJECT AREA

WISDOT CONTACT:


WI DEPT OF TRANSPORTATION
510 N HANSON LAKE ROAD
RHINELANDER, WI 54501
TELEPHONE: 715.365.5862
ATTENTION: NATHAN WHITE
EMAIL: NATHANIEL.WHITE@DOT.WI.GOV

DESIGN CONTACT:


SHORT ELLIOTT HENDRICKSON INC
6808 ODANA ROAD, SUITE 200
MADISON, WI 53719-1137
TELEPHONE: 608.620.6192
ATTENTION: CHRISTOPHER BLUM
EMAIL: CBLUM@SEHINC.COM

GENERAL NOTES:


- NO TREES OR SHRUBS SHALL BE REMOVED WITHOUT APPROVAL OF THE ENGINEER.
- THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.
- THE CONTRACTOR SHALL NOTIFY DIGGERS HOTLINE AND AFFECTED UTILITIES PRIOR TO THE START OF WORK. ANY LOCAL MUNICIPAL UTILITY WHICH IS NOT A MEMBER OF THE DIGGERS HOTLINE MUST BE CONTACTED SEPARATELY.
- PRIOR TO ORDERING DRAINAGE PIPES AND STRUCTURES, THE CONTRACTOR SHALL VERIFY RELATED DRAINAGE INFORMATION IN THE PLANS WITH THE ENGINEER.
- WETLANDS, WATERWAYS, AND OTHER ENVIRONMENTALLY SENSITIVE AREAS SHALL BE PROTECTED AT ALL TIMES. DO NOT STORE EQUIPMENT OR MATERIALS NEAR THESE SITES UNLESS APPROVED BY THE ENGINEER.
- INLET AND DISCHARGE ELEVATIONS FOR DRAINAGE STRUCTURES SHOWN ON THE PLAN MAY BE ADJUSTED BY THE ENGINEER TO FIT FIELD CONDITIONS.
- BROKEN CONCRETE CONTAINING RE-BAR SHALL NOT BE USED AS RIPRAP.
- CROSS SECTIONS SHOWN INCLUDE THE THICKNESS OF TOPSOIL WHERE REQUIRED. TOPSOIL SHALL BE REPLACED WITH 4-INCH TYPICAL DEPTH.
- TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.
- REMOVAL OF EROSION CONTROL DEVICES IS INCLUDED IN THE COST OF THEIR RESPECTIVE BID ITEMS.
- THE EROSION CONTROL FEATURES AS SHOWN IN THE PLANS ARE AT SUGGESTED LOCATIONS. EXACT LOCATIONS WILL BE DETERMINED BY THE ENGINEER IN THE FIELD.
- ASPHALTIC AND CONCRETE SURFACES SHALL BE SAWCUT AT THE MATCH LINE AS SHOWN ON THE PLAN OR AS DIRECTED BY THE ENGINEER.
- DISTURBED AREAS WITHIN THE RIGHT OF WAY, EXCEPT THE AREAS WITHIN THE FINISHED SHOULDER POINTS, SHALL BE TOPSOILED, FERTILIZED AND SEEDED.
- FERTILIZER SHALL NOT BE USED NEAR NAVIGABLE WATERWAYS OR WETLANDS.
- A CONVERSION FACTOR OF 2.0 TONS/CY IS USED TO ESTIMATE QUANTITIES FOR BASE AGGREGATE DENSE.
- APPLY TACK COAT AT A RATE OF 0.07 GAL/SY TO MILLED SURFACE AND 0.05 GA/SY BETWEEN LAYERS OF HMA PAVEMENT.
- HMA PAVEMENT WEIGHT CALCULATIONS ARE BASED ON 112 LB/SY/IN.
- THE CONTRACTOR'S PAVING OPERATIONS SHALL BE CONSISITENT WITH THE PLAN AND TYPICAL SECTIONS AND CONSTRUCTED TO PREVENT HMA LONGITUDINAL JOINTS FROM BEING LOCATED WITHIN A DRIVING, TURNING, PASSING OR PARKING LANE.

**TYPICAL EXISTING SECTION**



HAYMEADOW ROAD
STA 8+60 - STA 11+60

**TYPICAL PROPOSED SECTION**


HAYMEADOW ROAD
STA 8+60 - STA 11+60



✱ PROVIDE FOR THRIE BEAM GUARD RAIL ATTACHMENT.
① INDICATES WING NUMBER



PLAN
SINGLE SPAN FLAT SLAB



ELEVATION
NORMAL TO WATERWAY

THIS SHEET WAS CREATED BY THE WISDOT BUREAU OF STRUCTURES STANDARD BRIDGE DESIGN TOOL VERSION 1.1.0.0

STATE PROJECT NUMBER

9877-03-71

DESIGN DATA

LIVE LOAD:
DESIGN LOADING: HL-93
INVENTORY RATING FACTOR: RF = 1.07
OPERATING RATING FACTOR: RF = 1.39
WISCONSIN STANDARD PERMIT VEHICLE (WIS.-SPV): 250 (KIPS)

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

MATERIAL PROPERTIES:

CONCRETE MASONRY:
SUPERSTRUCTURE _____ $f'_c = 4,000$ P.S.I.
ALL OTHER _____ $f'_c = 3,500$ P.S.I.
BAR STEEL REINFORCEMENT:
GRADE 60 _____ $f_y = 60,000$ P.S.I.

FOUNDATION DATA

ABUTMENTS TO BE SUPPORTED ON HP 10 x 42 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 180 TONS \ddagger PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. PRE-BORING TO BE COMPLETED AT WEST ABUTMENT. ESTIMATED 15 FEET LONG AT WEST ABUTMENT AND 20 FEET AT EAST ABUTMENT.

\ddagger THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE DRIVEN PILE CAPACITY.

TRAFFIC VOLUME

HAYMEADOW ROAD
ADT = 72 (2026)
R.D.S. = 45 M.P.H.

HYDRAULIC DATA

100 YEAR FREQUENCY

$Q_{100} = 650.00$ C.F.S.
VEL. = 1.37 F.P.S.
 $HW_{100} = EL. 1570.75$
WATERWAY AREA = 506.64 SQ. FT.
DRAINAGE AREA = 21.00 SQ. MI.
ROADWAY OVERTOPPING = Y
SCOUR CRITICAL CODE = 5

2 YEAR FREQUENCY

$Q_2 = 225.00$ C.F.S.
VEL. = 1.36 F.P.S.
 $HW_2 = EL. 1569.19$

ROAD OVERTOPPING FREQUENCY

FREQUENCY = 4 YEARS
 $Q_4 = 300$ C.F.S.
 $HW_4 = EL. 1569.57$


LIST OF DRAWINGS


1. GENERAL PLAN
2. CROSS SECTION & QUANTITIES
3. SUBSURFACE EXPLORATION
4. WEST ABUTMENT
5. WEST ABUTMENT DETAILS
6. EAST ABUTMENT
7. EAST ABUTMENT DETAILS
8. SUPERSTRUCTURE
9. SUPERSTRUCTURE DETAILS
10. SINGLE SLOPE PARAPET 42SS

STRUCTURE DESIGN CONTACTS:

CHRIS BLUM 608-620-6192
AARON BONK 608-261-0261

THESE PLANS ARE BASED UPON STANDARD BRIDGE PLANS DEVELOPED AND MAINTAINED BY THE WISCONSIN DEPARTMENT OF TRANSPORTATION THROUGH THE USE OF THE WISDOT STANDARD BRIDGE DESIGN TOOL. THE UNDERSIGNED DESIGNER CERTIFIES THE ACCURACY OF THE BRIDGE TYPE, SIZE AND LOCATION, HYDRAULICS AND FOUNDATION SUPPORT, AND INFORMATION IN THE PLANS THAT IS NOT PART OF THE STANDARD PLANS SUPPLIED BY THE DEPARTMENT. THE DESIGNER FURTHER CERTIFIES THAT USE OF THE STANDARD BRIDGE DESIGN TOOL FOR DEVELOPMENT OF THIS PLAN IS CONSISTENT WITH THE GUIDANCE PROVIDED IN THE WISDOT BRIDGE MANUAL.



NO.	DATE	REVISION	BY
 SHORT ELLIOTT HENDRICKSON INC.			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED _____ DATE _____ CHIEF STRUCTURES DESIGN ENGINEER			
STRUCTURE B-43-70			
HAYMEADOW ROAD OVER HAYMEADOW CREEK			
COUNTY	ONEIDA	TOWN	PELICAN
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATION			
DESIGNED BY	JGM	DESIGNED CK'D	DKW
DRAWN BY	JGM	PLANS CK'D	CJB
GENERAL PLAN			SHEET 1 OF 10

I.D.

DATE:

SCALE = 12

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE ¾" UNLESS OTHERWISE NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES B-43-0070" SHALL BE THE EXISTING GROUNDLINE.

AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TYPE A.

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS.

THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TYPE HR TO THE EXTENT SHOWN ON SHEET 1 AND THE ABUTMENT DETAILS.

AT ABUTMENTS, CONCRETE POURED UNDER WATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 OF THE STANDARD SPECIFICATIONS.


SLAB FALSEWORK SHALL BE SUPPORTED ON PILES OR THE SUBSTRUCTURE UNLESS AN ALTERNATE METHOD IS APPROVED BY THE ENGINEER.

PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO ENTIRE EXPOSED TOP OF SLAB, THE TOP AND EXTERIOR EXPOSED FACE OF WINGS AND FRONT FACE OF ABUTMENT TO 1'-0" PAST THE EDGE OF SLAB.

PIGMENTED SURFACE SEALER TO BE APPLIED TO THE FRONT FACE AND TOP OF PARAPET.

BENCH MARK

NO.	STATION/OFFSET	DESCRIPTION	ELEV.
BM1	7+95.03/21.97' RT	SPK IN 16" PINE	1571.22
BM2	10+74.69/12.86' LT	¾" REBAR	1569.66
BM3	12+97.05/21.11' RT	SPK IN 20" PINE	1570.97




RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".


THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-43-70			
DRAWN BY JGM		PLANS CK'D CLB	
CROSS SECTION & QUANTITIES		SHEET 2	




CROSS SECTION THRU ROADWAY

LOOKING UPSTATION
(PILING NOT SHOWN FOR CLARITY)



ABUTMENT BACKFILL DIAGRAM

- L = ABUTMENT BODY LENGTH AT BACKFACE (FT)
- H = AVERAGE ABUTMENT FILL HEIGHT (FT)
- H1 = WING 1 HEIGHT AT TIP (FT)
- H2 = WING 2 HEIGHT AT TIP (FT)
- W = WING LENGTH (FT)
- EF = EXPANSION FACTOR (1.20 FOR CY BID ITEMS AND 1.00 FOR TON BID ITEMS)
- V_{CF} = (L)(3.0')(H) + (L)(0.5)(1.5H)(H) + (3')(0.5)(H1+H2+H+H)(W)
- V_{CY} = V_{CF}(EF)/27
- V_{TON} = V_{CY}(2.0)




PROFILE GRADE LINE

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER	WEST ABUT.	EAST ABUT.	TOTALS
203.0260	REMOVING STRUCTURE OVER WATERWAY WITH MINIMAL DEBRIS P-43-58	EACH	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-43-70	EACH	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	---	157	157	314
502.0100	CONCRETE MASONRY BRIDGES	CY	119	26	26	171
502.3200	PROTECTIVE SURFACE TREATMENT	SY	135	16	16	167
502.3210	PIGMENTED SURFACE SEALER	SY	50	---	---	50
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	---	2,050	2,050	4,100
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	26,180	1,520	1,520	29,220
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	---	6	6	12
550.0020	PRE-BORING ROCK OR CONSOLIDATED MATERIALS	LF	---	20	---	20
550.1100	PILING STEEL HP 10-INCH X 42 LB	LF	---	---	---	
606.0300	RIPRAP HEAVY	CY	---	---	---	
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	---	70	70	140
614.0150	ANCHOR ASSEMBLIES FOR STEEL PLATE BEAM GUARD	EACH	---	---	---	
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	---	43	43	86
645.0120	GEOTEXTILE TYPE HR	SY	---	---	---	
NON-BID ITEMS						
	FILLER	SIZE	---	---	---	½", ¾"
	NAMEPLATE	EACH	1	---	---	1
	BENCHMARK	EACH	1	---	---	1

THIS SHEET WAS CREATED BY THE WISDOT BUREAU OF STRUCTURES STANDARD BRIDGE DESIGN TOOL VERSION 1.1.0.0

PROTECTIVE SURFACE TREATMENT DETAILS





TYPICAL SECTION THRU ABUTMENT

▲ BACKFILL PAY LIMITS. BACKFILL BEYOND PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

■ PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.

BORING #	DATE COMPLETED
B-1	11-19-2024
B-2	11-19-2024
BORINGS COMPLETED BY: AMERICAN ENGINEERING TESTING, INC. 4203 SCHOFIELD AVENUE, SUITE 1 SCHOFIELD, WI 54476 (715) 359-3534	
REPORT COMPLETED BY: MATTHEW B. WILLIAMS, P.E.	
ALL COORDINATES REFERENCED TO WCCS NAD 83(91) ONEIDA COUNTY	



STATE PROJECT NUMBER

9877-03-71

MATERIAL SYMBOLS

ASPHALT

CONCRETE

SAND

BOULDERS OR COBBLES

SHALE

TOPSOIL

FILL

CLAY

LIMESTONE

SANDSTONE

PEAT

GRAVEL

SILT

BEDROCK (UNKNOWN)

IGNEOUS/META

LEGEND OF BORING

BORING #/EL.
STA./OFFSET

ST

0.25

17

F-C

COBBLE OR BOULDER

WEATHERED LIMESTONE

CORE RUN #1 - 24'-29'

REC=80%, RQD=72%

(1)

UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2)

UNLESS OTHERWISE, SPECIFIED THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

▽

AT TIME OF DRILLING

▼

END OF DRILLING

▼

AFTER DRILLING

ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE


SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION


BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-43-70			
DRAWN BY ZLM		PLANS CK'D JGM	
SUBSURFACE EXPLORATION		SHEET 3	


8

8





9		PROJECT NO: 9877-03-71			HWY: LOCAL (HAYMEADOW RD)			COUNTY: ONEIDA			CROSS SECTIONS: HAYMEADOW ROAD			SHEET		E	9
---	--	------------------------	--	--	---------------------------	--	--	----------------	--	--	--------------------------------	--	--	-------	--	---	---



9

9

PROJECT NO: 9877-03-71	HWY: LOCAL (HAYMEADOW RD)	COUNTY: ONEIDA	CROSS SECTIONS: HAYMEADOW ROAD	SHEET E
------------------------	---------------------------	----------------	--------------------------------	---------